



MATERIAL SAFETY DATA SHEET



MANUFACTURER'S NAME
THE DPI CO.,LTD
615 PAKDAL-DONG,MANAN-KU
ANYANG-CITY, KYUNGGI-DO,KOREA

EMERGENCY TELEPHONE NO
(080)944-7777

DATE OF PREPARATION
20-Nov-01

INFORMATION TELEPHONE NO.
(031)467-6167

Section - PRODUCT IDENTIFICATION

Section - SPILL OR LEAK PROCEDURES

PRODUCT NUMBER
PRODUCT NAME HIQ Blending Thinner DR-500
PRODUCT CLASS
HMIS CODES
Health -2
Flammability -3
Reactivity -0

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED
Remove all sources of ignition. Ventilate and remove with inert absorbent.
WASTE DISPOSAL METHOD
Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act(RCRA) 40 CFR 261.

Section -HAZARDOUS INGREDIENTS

Table with columns: CAS No., HAZARDOUS INGREDIENTS, %by WT, ACGIH TLV, ISH-KOREA, UNITS, V.P. (mm HG)

Incinerate in approved facility. Do not incinerate closed container.
Dispose of in accordance with Federal, State, and Local regulations regarding pollution.

Section -PROTECTION INFORMATION

Section -PHYSICAL DATA
PRODUCT WEIGHT -- N.A
SPECIFIC GRAVITY -- 0.90±0.1
BOILING POINT -- 135-210
VOLATILE VOLUME -- 100%

PRECAUTIONS TO BE TAKEN IN USE
NO PERSON SHOULD USE THIS PRODUCT, OR BE IN AREA WHERE IT IS BEING USED, IF THEY HAVE CHRONIC (LONG-TERM) LUNG OR BREATHING PROBLEMS OR IF THEY EVER HAD A REACTION TO ISOCYANATES.
Use only with adequate ventilation. Avoid breathing vapor and spray mist.
Avoid contact with skin and eyes. Wash hands after using.
This coating may contain materials classified as nuisance particulates (listed "as Dust" in Section\_) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section\_, the applicable limits for nuisance dusts are ACGIH TLV 10 mg./m3(total dust), OSHA PEL 15 mg./m3(total dust), 5mg./m3(respirable fraction)
VENTILATION
Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section\_ is maintained below applicable exposure limits.

Section -FIRE AND EXPLOSION HAZARD DATA

FLASH POINT -4
FLAMMABILITY CLASSIFICATION 1

RESPIRATORY PROTECTION
Where overspray is present, a positive pressure air supplied respirator (TC19C NIOSH/MSHA approved) should be worn. If unavailable, a properly protection against materials in Section\_ may be effective. Follow respirator manufacturer's directions for use. Wear the respirator for the whole time of spraying and until all vapors and mists are gone.NO PERSONS SHOULD BE ALLOWED IN THE AREA WHERE THIS PRODUCT IS BEING USED UNLESS EQUIPPED WITH THE SAME RESPIRATOR PROTECTION RECOMMENDED FOR THE PAINTERS.

EXTINGUISHING MEDIA
carbon dioxide, dry chemical, foam

UNUSUAL FIRE AND EXPLOSION HAZARDS
Keep containers tightly closed. Isolate from heat, electrical equipment, sparks, and open flame. Closed containers may explode when exposed to extreme heat. Application to hot surfaces requires special precautions. During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.
SPECIAL FIRE FIGHTING PROCEDURES
Full protective equipment including self-contained breathing apparatus should be used. Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

PROTECTIVE GLOVES
Wear gloves which are recommended by glove supplier for protection against materials in Section\_
EYE PROTECTION
Wear safety spectacles with unperforated sideshields.
OTHER PROTECTIVE EQUIPMENT
Use barrier cream on exposed skin.

Section -HEALTH HAZARD DATA

ROUTES OF EXPOSURE
Exposure may be by INHALATION and/or SKIN or EYE contact, depending on conditions of use. To minimize exposure, follow recommendations for proper use, ventilation, and personal protective equipment.
ACUTE Health Hazards
EFFECTS OF OVEREXPOSURE
Irritation of eyes, skin and respiratory system. May cause nervous system depression. Exterme overexposure may result in unconsciousness and possibly death.
SIGNS AND SYMPTOMS OF OVEREXPOSURE
Redness and itching or burning sensation may indicate eye or excessive skin exposure.
Headache, dizziness, nausea, and loss of coordination are indications of excessive exposure to vapors or spray mists.
MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE
May cause allergic respiratory and/or skin reaction in susceptible persons or sensitization. This effect may be delayed several hours after exposure.
EMERGENCY AND FIRST AID PROCEDURES
If INHALED: If any breathing problems occur during use, LEAVE THE AREA and get fresh air.If problems remain or occur later,IMMEDIATELY get medical attention.
If on SKIN: Wash affected area thoroughly with soap and water. Remove contaminated clothing and launder before re-use.
If in EYES: Flush eyes with large amounts of water for 15 minutes. Get medical attention.
If SWALLOWED: Get medical attention.
CHRONIC Health Hazards
No ingredient in this product is an IARC,NTP or OSHA listed carcinogen. Prolonged overexposure to solvent ingredients in Section\_ may cause adverse effects to the liver, urinary, blood forming, cardiovascular and reproductive systems.
Persons sensitive to isocyanates will experience increased allergic reaction on repeated exposure.

Section -PRECAUTIONS

DOL STORAGE CATEGORY-1B
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING
Contents are FLAMMABLE. Keep away from heat, sparks, and open flame. During use and until all vapors are gone: Keep area ventilated-Do not smoke - Extinguish all flames, pilot lights, and heaters - Turn off stoves, electric tools and appliances, and any other sources of ignition. Consult NFPA Code. Use approved Bonding and Grounding procedures. Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not take internally.
KEEP OUT OF THE REACH OF CHILDREN.
OTHER PRECAUTIONS
This product must be mixed with other components before use. Before opening the packages, READ AND FOLLOW WARNING LABELS ON ALL COMPONENTS. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

Section -REACTIVITY DATA

STABILITY -- stable
INCOMPATIBILITY None known
HAZARDOUS DECOMPOSITION PRODUCTS -By fire;Carbon dioxide, Carbon Monoxide
HAZARDOUS POLYMERIZATION -Will not Occur

The above information pertains to this product as currently formulated, and is based on the information available at this time.Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control,we make no warranties, express or implied, and assume no liability in connection with any use of this information.